

REFRIGERATION

COMMERCIAL REFRIGERATION

Certified distributor of



Conforms to NSF/ANSI7 (ETL)



WARRANTY
3 Years Parts and Labor
5 Years on compressor in USA

SANDWICH PREP TABLES

- Stainless steel interior and exterior
- Self-contained rear mounted compressor for easy maintenance
- R-290 Hydrocarbon refrigerant-increases energy efficiency by up to 25%
- High density Cyclopentane insulation (HFC-free)
- 4" swivel casters with brakes
- Self-closing door with lifetime guaranteed metal handles
- Foam insulated stainless steel roll back lid with 2 step lid stops
- Epoxy coated wire shelves adjustable in 1" increments
- Temperature range 33° - 39° F
- 9' 8" cord
- 115V 60Hz



JMG-BAPT28

Model	Doors/Shelves	Capacity	Dimensions	Amps	Net Wt.
JMG-BAPT28	1/1	7 cu. ft.	27.5" x 33" x 42.5"	4.0	157 lbs
JMG-BAPT36	2/2	9.5 cu. ft.	36.5" x 33" x 42.5"	4.1	187 lbs
JMG-BAPT48	2/2	13.1 cu. ft.	48.5" x 33" x 42.5"	4.5	223 lbs
JMG-BAPT60	2/2	16.7 cu. ft.	60.5" x 33" x 42.5"	4.7	258 lbs
JMG-BAPT72	3/3	20.2 cu. ft.	72.5" x 33" x 42.5"	5.3	309 lbs



JMG-BAPT36



JMG-BAPT48



JMG-BAPT60



JMG-BAPT72

MEGA TOP SANDWICH TABLES

- Stainless steel interior and exterior
- Self-contained rear mounted compressor for easy maintenance • Oversized refrigeration unit
- R-290 Hydrocarbon refrigerant-increases energy efficiency by up to 25%
- High density Cyclopentane insulation (HFC-free)
- 4" swivel casters with brakes
- Self-closing door with lifetime guaranteed metal handles
- Foam insulated stainless steel roll back lid with 2 step lid stops
- Epoxy coated wire shelves adjustable in 1" increments
- Temperature range 33° - 39° F
- 9' 8" cord
- 115V 60Hz



JMG-BAMT28

Model	Doors/Shelves	Capacity	Dimensions	Amps	Net Wt.
JMG-BAMT28	1/1	7 cu. ft.	27.5" x 37.25" x 44"	4.1	161 lbs
JMG-BAMT36	2/2	9.5 cu. ft.	36.5" x 37.25" x 44"	4.1	190 lbs
JMG-BAMT48	2/2	13.1 cu. ft.	48.5" x 37.25" x 44"	4.7	227 lbs
JMG-BAMT60	2/2	16.7 cu. ft.	60.5" x 37.25" x 44"	4.9	276 lbs
JMG-BAMT72	3/3	20.2 cu. ft.	72.5" x 37.25" x 44"	5.4	311 lbs



JMG-BAMT36



JMG-BAMT48



JMG-BAMT60



JMG-BAMT72

UNDERCOUNTER REFRIGERATORS

- Stainless steel interior and exterior
- Self-contained rear mounted compressor for easy maintenance • Oversized refrigeration unit
- R-290 Hydrocarbon refrigerant-increases energy efficiency by up to 25%
- High density Cyclopentane insulation (HFC-free)
- 4" swivel casters with brakes
- Self-closing door with lifetime guaranteed metal handles
- Foam insulated stainless steel roll back lid with 2 step lid stops
- Epoxy coated wire shelves adjustable in 1" increments
- Temperature range 33° - 39° F
- 9' 8" cord
- 115V 60Hz



JMG-BAUR28

Model	Doors/Shelves	Capacity	Dimensions	Amps	Net Wt.
JMG-BAUR28	1/2	7 cu. ft.	27.5" x 33" x 37.75"	3.6	139 lbs
JMG-BAUR36	2/4	9.5 cu. ft.	36.5" x 33" x 37.75"	3.8	163 lbs
JMG-BAUR48	2/4	13.1 cu. ft.	48.5" x 33" x 37.75"	3.9	196 lbs
JMG-BAUR60	2/4	16.7 cu. ft.	60.5" x 33" x 37.75"	4.7	225 lbs
JMG-BAUR72	3/6	20.2 cu. ft.	72.5" x 33" x 37.75"	5.2	263 lbs



JMG-BAUR36



JMG-BAUR48



JMG-BAUR60



JMG-BAUR72

UNDERCOUNTER FREEZER

- Stainless steel interior and exterior
- Self-contained rear mounted compressor for easy maintenance • Oversized refrigeration unit
- R-290 Hydrocarbon refrigerant-increases energy efficiency by up to 25%
- High density Cyclopentane insulation (HFC-free)
- 4" swivel casters with brakes
- Self-closing door with lifetime guaranteed metal handles
- Foam insulated stainless steel roll back lid with 2 step lid stops
- Epoxy coated wire shelves adjustable in 1" increments
- Temperature range -10° - 5° F
- 9' 8" cord
- 115V 60Hz
- NSF /ANSI Standard 7 Compliant



JMG-BAUF28

Model	Doors/Shelves	Capacity	Dimensions	Amps	Net Wt.
JMG-BAUF28	1/2	7 cu. ft.	27.5" x 33" x 37.75"	3.2	139 lbs
JMG-BAUF36	2/4	9.5 cu. ft.	36.5" x 33" x 37.75"	5.2	172 lbs
JMG-BAUF48	2/4	13.1 cu. ft.	48.5" x 33" x 37.75"	6.0	205 lbs
JMG-BAUF60	2/4	16.7 cu. ft.	60.5" x 33" x 37.75"	6.2	238 lbs



JMG-BAUF36



JMG-BAUF48



JMG-BAUF60

SWING DOOR REFRIGERATORS & FREEZERS

- Stainless steel interior and exterior
- Self-contained bottom mounted compressor for easy maintenance
- Oversized refrigeration unit
- R-290 Hydrocarbon refrigerant-increases energy efficiency by up to 25%
- High density cell polyurethane insulation (CFC-free)
- Self Diagnostic digital temperature control with open door alarm
- Self-closing and stay open door with metal handles and door locks
- LED interior lighting
- 4 shelves per door section with 1" adjustable shelving heights
- Refrigerator temperature range 29° - 39° F / Freezer -10° - 5° F
- 4" swivel casters with front brakes
- 9'8" cord
- 115V 60Hz



JMG-BSR-HC1 / JMG-BSF-HC1

Model	Doors/Shelves	Capacity	Dimensions	Amps	Net Wt.
REFRIGERATORS					
JMG-BSR-HC1	1/4	23 cu. ft.	26.75" x 32.375" x 82.375"	2.0	238 lbs
JMG-BSR-HC2	2/8	49 cu. ft.	54" x 32.375" x 82.375"	2.4	373 lbs
JMG-BSR-HC3	3/12	72 cu. ft.	81" x 32.375" x 82.375"	5.5	615 lbs
FREEZERS					
JMG-BSF-HC1	1/4	23 cu. ft.	26.75" x 32.375" x 82.375"	5.6	251 lbs
JMG-BSF-HC2	2/8	49 cu. ft.	54" x 32.375" x 82.375"	6.6	403 lbs
JMG-BSF-HC3	3/12	72 cu. ft.	81" x 32.375" x 82.375"	9.9	626 lbs



JMG-BSR-HC2 / JMG-BSF-HC2



JMG-BSR-HC3 / JMG-BSF-HC3