## **ALUMINUM PLATFORM TRUCKS**

- Constructed of all welded 1"x 16ga sq tubular aluminum
- (4) Swivel casters with 5" x 1.25" polyurethane non-marking wheels 250lbs capacity per wheel, evenly distributed
- 6 wheeled models have (2) rigid casters with 8" mold on center wheels 800lbs capacity per wheel evenly distributed
- 16ga diamond plate on diamond plate modelsAluminum guaranteed against rust or corrosion.



JM-AL-DPLT-2436

Model	Dimensions	# of Wheels	Shipping Weight
JM-AL-PT-1842-6	18"x42"x39"	6	43 lbs
JM-AL-PT-1853-6	18"x53"x39"	6	48 lbs
JM-AL-PT-3060-NST	33"x60"x39"	4	76 lbs
JM-AL-PT-3060	33"x60"x39"	4	58 lbs
JM-AL-DPLT-2436*	24"x36"x39"	4	42 lbs
* (4) 5" x2" polyurethane w	heels		



JM-AL-PT-3060-NST

## **STEEL PLATFORM TRUCKS**

JM-AL-PT-1842-6

- Constructed of all welded 1"x16ga steel tubing frame
- (4) Swivel casters with 5" x 1.25" polyurethane non-marking wheels 250lbs capacity per wheel, evenly distributed
- J-PT-2448, J-WD-2754-2H (2) 8"x 2" swivel; (2) 8" x2" rigid
- 6 wheeled models have (2) rigid casters with 8" mold on center wheels 800lbs capacity per wheel evenly distributed
- Powder coated finish

Model	Dimensions	# of Wheels	Shipping Weight		
	1.0"	4	20 //		
J-PT-1842-4*	18"x42"x39"	4	38 lbs		
J-PT-1842-6	18"x42"x39"	6	55 lbs		
J-PT-1853-6	18"x53"x39"	6	65 lbs		
J-PT-1836-SB	18"x36"x39"	6	52 lbs		
J-PT-2448	24"x48"x 39"	4	80 lbs		
*J-PT-1842-4 has (2) rigid and (2) swivel 5"x 1.25"					



Model	Dimensions	# of Wheels	Shipping Weight
J-WD-2754-2H	27"x54"x32"	4	97 lbs